

Cooker Hood



To compliment the existing range of ventilation products, Ferrob are now able to offer a newly-developed range of cooker hoods for domestic kitchens.

Having two colours across two models enables Ferrob to fully ventilate a property whatever the circumstances to suit all tastes.

All units come in either white or brown with integral grease filters, 3-speed switch and light.

- ✿ Extract Rate maximum 180m³/hr
- ✿ Low Running Costs
- ✿ British Made
- ✿ 2 year no quibble guarantee
- ✿ Meets Building Regulations 2006
- ✿ 3-speed operation as standard
- ✿ Easy to install
- ✿ Quiet in operation
- ✿ **CE**

Technical Data

Catalogue No.	Type
CK100	Complete with 3-speed manual switch.
CK100T	As above but with over-run timer for internal kitchens.
Both models carry a suffix of W for white or B for brown.	

Construction	These units are made of strong and durable powder-coated steel for strength, durability and finish.
Electrical	220-230V ~ A.C. 50Hz Single phase consuming 90 watts when on fast speed and 27 watts on slow continuous speed. These units require an earth. All wiring must comply with current IEE regulations. A double pole isolating switch, having a contact separation of at least 3mm in all poles, must be used with a 3 amp fuse fitted.
Motor	Single phase three-speed induction motor with pre-oiled ball-bearings for a long maintenance free life and protected by a thermal fuse.
Guarantee	Two year no quibble guarantee.
Installation	The units are designed to be mounted above the cooker or hob. It is recommended that the unit is ducted out through the wall or through flat ducting if the hood is on an internal wall.

Performance	CK100 / CK100T - Maximum Extract Rate 180m ³ /hr
Additional Data	Maximum pressure: 50 pa. Noise level - full speed: 25.0 dB(A). Maximum operating temperature: -40°C. Unit Dimensions: -W 600, D 500, H 150